



1600 Series Electric Strikes

DynaLock 1600 Series Electric Strikes are universally adaptable to suit all door and frame types and accommodate most locking devices with up to a 3/4" latch projection. To simplify ordering and speed installation all 1600 Series models feature 12/24V AC/DC field-selectable operation, dial-selectable fail-safe or fail-secure operating mode, 1/4" horizontal adjustment and modular, plug-in wire connections. All models are also available in a low-profile, 1-1/16" backset version, for narrow-style aluminum frames, which accept up to a 5/8" latch projection. Optional latch/keeper monitor switches are also available.

Current Draw: 0.375 Amps @ 12VDC; 0.565 Amps @ 12VAC
0.190 Amps @ 24VDC; 0.280 Amps @ 24VAC

MODEL	PRODUCT	FINISH	LIST PRICE
1604S	Aluminum/Wood Frames, Std. Profile, 1-1/4" x 4-7/8"	US32D	174.00
1604L	Aluminum/Wood Frames, Low Profile, 1-1/4" x 4-7/8"	US32D	174.00
1614S	Steel/Wood Frames, Std. Profile, 1-1/4" x 4-7/8"	US32D	174.00
1614L	Steel/Wood Frames, Low Profile, 1-1/4" x 4-7/8"	US32D	174.00
1605S	Aluminum/Wood Frames, Std. Profile, 1-1/8" x 5-7/8"	US32D	179.00
1605L	Aluminum/Wood Frames, Low Profile, 1-1/8" x 5-7/8"	US32D	179.00
1607S	Aluminum/Wood Frames, Std. Profile, 1-1/4" x 6-7/8"	US32D	179.00
1607L	Aluminum/Wood Frames, Low Profile, 1-1/4" x 6-7/8"	US32D	179.00
1608S	Aluminum/Wood Frames, Std. Profile, 1-7/16" x 7-15/16"	US32D	185.00
1608L	Aluminum/Wood Frames, Low Profile, 1-7/16" x 7-15/16"	US32D	185.00

1661 Series Electric Rim Strikes

DynaLock 1661 Series Electric Rim Strikes are universally adaptable to suit all door and frame types and accommodate Pullman latch rim exit devices with up to a 3/4" latch projection. To simplify ordering and speed installation, the 1661 Series models feature AC/DC operation (specify 12 or 24V), are fully reversible for left or right hand doors, and are horizontally adjustable to compensate for door misalignment. For surface applications a frame depth of 1-5/8" is required (for the electrical insert). Specify the RMP option for semi-mortise installations. For double door installations specify the DDH option to allow mounting of the 1661 on the inactive door leaf.

Current Draw: 0.20 Amps @ 12VDC; 0.15 Amps @ 12VAC
0.11 Amps @ 24VDC; 0.07 Amps @ 24VAC



MODEL	PRODUCT	FINISH	LIST PRICE
1661-12	Fail Secure, 12 VAC/VDC, 1-3/4" x 9"	US32D	300.00
1661-24	Fail Secure, 24 VAC/VDC, 1-3/4" x 9"	US32D	300.00

1600 & 1661 SERIES OPTIONS

		LIST PRICE
LMS	Lock Monitor Switches - Indicate latch and keeper status. For the 1600 Series.	50.00
SF	Special Finishes - US32D standard. US3, US4, US10, US10B and US32 available. For the 1600 Series.	28.00
DDH	Double Door Housing. For the 1661 Series.	148.00
RMP	Rear Mounting Plate - Kit for semi-mortise installations or reinforcement in surface applications. For the 1661 Series.	36.00

