

2013 Series 1200 Lb. Gate Lock



2013

Electromagnetic lock, surface mounted for sliding or swinging gates. Face drilled mounting holes, weather resistant, sealed 1/2" NPT conduit fitting with six foot long 18AWG leads.
 Field selectable 12/24 VDC
 Size: 1-1/2"D x 2-1/2"H x 9-1/4"L
 Current Draw: 0.42 Amps @ 12VDC
 0.21 Amps @ 24VDC



NYC MEA
 #23-92-E

MODEL	PRODUCT	FINISH	LIST PRICE
2013	Single Gate Lock - 12/24 VDC	US28	433.00

OPTIONS		LIST PRICE
DYN	Dynastat Force Sensor - Indicates efficient magnetic bond.	66.00
GLB	Gate Lock Bracket - Fully adjustable "Z" bracket for swinging gate applications.	111.00
GLB2	Gate Lock Bracket - "L" Brackets for sliding gate application.	137.00
RWE	Rear Wire Exit - Coil wiring exits from back of housing in lieu of conduit nipple.	N/C
SF	Special Finish - Standard finish US28. Special anodized finishes see page 47.	

Notes: For AC operation order #7088 Pre-wired Rectifier Bridge. See page 40.

2600 Series 650 Lb. Mortise Lock



2600

Electromagnetic lock, mortise mounted for sliding door.
 Field selectable 12/24 VDC
 Size: 1-1/2"W x 8-3/4"H x 1-1/8"D
 Current Draw: 0.50 Amps @ 12VDC
 0.25 Amps @ 24VDC

MODEL	PRODUCT	FINISH	LIST PRICE
2600	Single Mortise Lock - 12/24 VDC	US28	346.00

OPTIONS		LIST PRICE
AMB	Armature Mounting Block	53.00
DYN	Dynastat Force Sensor - Indicates efficient magnetic bond.	66.00
MB	Mounting Brackets - Two piece kit.	21.00
SF	Special Finish - Standard finish US28. Special anodized finishes see page 47.	

Notes: For AC operation order #7088 Pre-wired Rectifier Bridge. See page 40.