

2500 Series 650 Lb. "Mini"



2511

Mini electromagnetic locks, surface mounted for single and double outswing or inswing doors.
 Size: 1-1/4"D x 1-3/4"H x 10-1/2"L Single or 21"L Double
 Multi-voltage field selectable 12/24 VAC/VDC
 Current Draw: 0.50 Amps @ 12V Single / 1 Amp Double
 0.25 Amps @ 24V Single / 0.50 Amps Double



2522

MODEL	PRODUCT	FINISH	LIST PRICE
2511	Single Electromagnetic Lock Outswing	US28	340.00
2522	Double Electromagnetic Lock Pair Outswing	US28	680.00
2511TJ	Single Electromagnetic Lock Inswing	US28	422.00
2522TJ2	Double Electromagnetic Lock Pair Inswing	US28	844.00



2511TJ

OPTIONS		LIST PRICE
ATS	Anti-Tamper Switch - Signals removal of the housing cover.	44.00
CLH	Custom Length Housing - See page 19.	
DSM	Door Status Switch - Signals door closed or ajar.	56.00
DSM2	Door Status Switch - For the 2522 Series.	112.00
DYN	Dynastat Force Sensor - Indicates efficient magnetic bond.	66.00
DYN2	Dynastat Force Sensor - For the 2522 Series.	132.00
LED	Bi-Color LED - For local signaling of lock status. (Requires DYN Option. Not available on TJ models.)	36.00
LED2	Bi-Color LED's (2) - For the 2522 Series. (Requires DYN2 Option. Not available on TJ models.)	72.00
SF	Special Finish - Standard finish US28. Special anodized finishes see page 47.	



2522TJ2

