



5025



NYC MEA
#23-92-E

Battery Back-Up Time

TOTAL CURRENT DRAW	BATTERY SIZE	
	4AH	7AH
0.25A	13.3hrs	23.3hrs
0.5A	6.6hrs	11.7hrs
0.75A	4.4hrs	7.8hrs
1A	3.3hrs	5.8hrs

NOTE: Estimated times shown.
Battery condition, temperature, and other factors may affect performance.

5025 Series Single Zone

- Field selectable voltage output: 12VDC or 24VDC.
- Power output: 1 Amp @ 12/24VDC.
- Filtered and regulated voltage output.
- Built-in battery charging circuit.
- Choice of 4 or 7 Amp/Hour battery back-up capacity.
- May be connected to fire alarm with N.C. contacts.
- 15" x 12" x 4" hinge cover steel enclosure with knockouts.

MODEL	PRODUCT	LIST PRICE
5025	Power Supply with direct output and built-in battery charging circuit.	219.00

OPTIONS		LIST PRICE
ATS	Anti-Tamper Switch - Signals opening of enclosure cover.	44.00
BBU1-4	Battery Back-up - 4 AH @ 12VDC, 1 battery.	66.00
BBU1-7	Battery Back-up - 7 AH @ 12VDC, 1 battery.	95.00
BBU2-4	Battery Back-up - 4 AH @ 24VDC, 2 batteries.	132.00
BBU2-7	Battery Back-up - 7 AH @ 24VDC, 2 batteries.	190.00
CAB	Cable Kit - For third party batteries (Included at no charge with all BBU options).	21.00
KLC	Key Locked Cover - Includes two keys.	38.00
PC	Power Cord - Six foot, pre-connected, 3-wire line cord with ground.	32.00

Power Supply Lock Capacity Chart

OUTPUT VOLTAGE	MAX LOAD	LOCKING DEVICE					
		1300	2511	2011/3000	2268-10	3006	3101B
12VDC	1A	1	1	2	1	1	1
24VDC	1A	2	3	4	2	3	1
RATINGS PER LOCK		0.85A@12V 0.45A@24V	0.50A@12V 0.25A@24V	0.42A@12V 0.21A@24V	0.68A@12V 0.35A@24V	0.50A@12V 0.30A@24V	0.75A@12V 0.50A@24V