



7001xCYL



7001xNRxCYL



7050

7000 Series Keyswitches

Keyswitches may be used to control electric locks, shunt or activate security panels, consoles or any similar requirements. The assembly is supplied with face plate, bracketry, cylinder locknut and one or two switches depending on model ordered. The user typically supplies the mortise cylinder and cam when master keying a system. Models 7050 & 7051 do not require a cylinder.

Switch contacts rated 6 Amps @ 125VAC and are available momentary or maintained, SPDT or DPDT. Switch assembly requires 1-1/2" depth clearance and is shipped on single, double or narrow gang plates. Standard Finish: US32D

Cylinder Requirements: 1-1/8" or 1-1/4" Mortise Cylinder with "bat" type cam.

MODEL	PRODUCT	LIST PRICE
7001	Maintained, (1) SPDT	127.00
7002	Momentary, (1) SPDT	116.00
7003	Maintained, (2) SPDT	155.00
7004	Momentary, (2) SPDT	133.00
7005	Momentary/Maintained, 1 Each SPDT	143.00
7021	Maintained, (1) DPDT	154.00
7022	Momentary, (1) DPDT	143.00
7023	Maintained, (2) DPDT	199.00
7024	Momentary, (2) DPDT	177.00
7025	Momentary/Maintained, 1 Each DPDT	184.00
7035	Elec. Time Delay, 0-60 Sec. SPDT, 2 Gang	266.00
7050	3101B Type, Momentary/Maintained	89.00
7051	3101B Type, Momentary/Momentary	127.00

OPTIONS	LIST PRICE
* ATS	Anti-Tamper Switch 42.00
◦ AUD	Audible Sounder - 1-28VDC (Requires DBL option). 18.00
• CYL	Mortise Cylinder - 1-1/4" long w/cam, 2 keys. 38.00
DBL	Two Gang Plate - 4-9/16" wide, for options. 6.00
KEY	Key, Extra (Order with CYL option) 6.00
LED	Bi-Color LED - Red/Green, 12/24VDC. 32.00
NR	Narrow Plate - 1-3/4" wide, substitute. 6.00
PB	Pushbutton - 6115 type (Requires DBL option). 59.00
SF	Special Finishes - Standard finish US32D. See page 47.
◦ WPC	Weatherproof Cover - Single gang only. 16.00

Notes: * Not available with NR option.
 ◦ Not available on 7035.
 • All cylinders keyed alike.