

7075 Series Break Glass Exit Stations



7075

Break glass assembly provides auxiliary method of releasing egress doors in an emergency situation. The assembly may be ordered in three versions: standard, standard with LED indicator or standard with audible.

Size: 6-3/4" x 4-1/2"

Contacts: SPDT-DB (FORM Z), MOM rated 6 Amps @ 125VAC

Furnished with 5 spare glass lenses.



MODEL	PRODUCT	LIST PRICE
7075	Break Glass, Standard	255.00
7076	Break Glass, with Bi-Color LED, Red/Green, 12/24VDC	289.00
7077	Break Glass, with Audible Sounder, 1-28VDC, 1-28VDC	300.00
7078	Spare Contact Block, SPDT	65.00
7079	Spare Lenses, 5 Pk.	44.00

7080 Series Adjustable Time Delay Module



7080

Compact, in-line time delay module provides an adjustable relock delay for an electric lock controlled by a momentary normally-closed access/egress device.


Size: 5/8"W x 2"L x 9/16"D

Input Power: 12-30 VAC/VDC, Contacts: SPDT rated 1 Amp @ 30VDC

Delay Adjustment Range: 0-60 Seconds

MODEL	PRODUCT	LIST PRICE
7080	Adjustable Time Delay Module	69.00

7086 Series Programmable Digital Timer



7086

365 day/24 hour digital timer provides automated control of electric locks.

Programmable for up to 50 weekly/daily events and 10 holidays. Operates on 12 or 24 VAC/VDC @ 0.05A.

Size: 3"W x 5.25"L x 1"D

Contacts: SPDT rated 10 Amps @ 120VAC

MODEL	PRODUCT	LIST PRICE
7086	Programmable Digital Timer	354.00

7088 Prewired Rectifier



7088

MODEL	PRODUCT	LIST PRICE
7088	1 Amp Prewired Rectifier Module	21.00