

1700 Series Fire-Labeled Electric Strikes

DynaLock 1700 Series Fire-Labeled Electric Strikes accommodate cylindrical, center line mortise, and narrow-line aluminum lock sets, along with mortise exit devices, with up to 3/4" latch projection (non-Pullman type). An enlarged latched cavity width allows compatibility with 3-piece, anti-friction latches. Fail-secure lock mode is standard and 12V and 24V models accept AC/DC input. All models are fully reversible for left or right-hand doors and standard mounting tabs and installation fasteners are included. Radius or square corner, US32D Stainless Steel, ANSI 4-7/8" x 1-1/4" faceplates are available.



1704



1714

MODEL	PRODUCT	FINISH	LIST PRICE
1704-12	Aluminum Frames, Radius Corners, 12VAC/VDC	US32D	310.00
1704-24	Aluminum Frames, Radius Corners, 12VAC/VDC	US32D	310.00
1714-12	Aluminum/Hollow Metal Frames, Square Corners, 12VAC/VDC	US32D	310.00
1714-24	Aluminum/Hollow Metal Frames, Square Corners, 12VAC/VDC	US32D	310.00


All models are Fire-Labeled, UL 10C (1-1/2 hr.) and UL 1034 Burglary-resistant.

Current Draw (Sound): 0.15 Amps @ 12VDC (Silent)
 0.20 Amps @ 12VDC (Buzz)
 0.07 Amps @ 24VDC (Silent)
 0.11 Amps @ 24VDC (Buzz)



1800 Series Fire-Labeled Heavy-Duty Electric Strikes

DynaLock 1800 Series Fire-Labeled Heavy-Duty Electric Strikes accommodate cylindrical, center line mortise, and narrow-line aluminum lock sets, along with mortise exit devices, with up to 3/4" latch projection (non-Pullman type). All models are non-handed, feature horizontal adjustable (up to 1/4"), internal solenoid and a heavy-duty, cast stainless steel (US32D) housing. Additionally a concealed pry-guard and saddle-mount housing design enhance strength, durability and tamper resistance. Fail-secure lock mode is standard and 12V and 24V models accept AC/DC input. Choice of ANSI 4-7/8" x 1-1/4" (1814) or 9" x 1-3/8" (1819) faceplates.



1814



1819

MODEL	PRODUCT	FINISH	LIST PRICE
1814-12	4-7/8" x 1-1/4" Faceplate, 12VAC/VDC	US32D	370.00
1814-24	4-7/8" x 1-1/4" Faceplate, 24VAC/VDC	US32D	370.00
1819-12	9" x 1-3/8" Faceplate, 12VAC/VDC	US32D	410.00
1819-24	9" x 1-3/8" Faceplate, 24VAC/VDC	US32D	410.00

All models are Fire-Labeled, UL 10C (1-1/2 hr.) and UL 1034 Burglary-resistant.

Current Draw (Sound): 0.15 Amps @ 12VDC (Silent)
 0.20 Amps @ 12VDC (Buzz)
 0.07 Amps @ 24VDC (Silent)
 0.11 Amps @ 24VDC (Buzz)



Fits Frames cut out for:

Folger Adam 712 (1814)

Folger Adam 310-2 (1819)

Von Duprin 6211 ANSI (1814)

Von Duprin 6215 (1819)

Von Duprin 6226 (1819)