

# 6170 Series

## Weatherproof Pushbutton

- **Commercial Grade**
- **Sealed Against Moisture & Dust**
- **Variety of Signage Options**
- **Green LED Backlight**
- **Lifetime Warranty**



SHOWN WITH LED BACKLIGHT ILLUMINATED

### Description

The 6170 Series Weatherproof Pushbutton features a commercial-grade switch assembly, completely sealed against moisture and dust intrusion. It is specifically designed to withstand outdoor exposure to the elements and other harsh environments.

The standard 3/4" diameter white, raised dome pushbutton includes a green LED backlight, selectable for 12 or 24VDC operation. Momentary-action, SPDT double-break contacts are standard on all models. The 6170 Series is ideally suited for exposed use as a momentary release or request-to-exit control for electric locks on doors and gates, in most commercial, industrial and institutional applications.

### Standard Features

- **Water-tight to IP68:** Button assembly is rated for immersion in water up to 1 meter.
- **Moisture-proof to IP64:** Button assembly is rated for exposure to water splashing from any direction.
- **Dust-tight to IP64:** Button assembly is rated for protection from dust ingress.
- **Thermoplastic Button** integrated with a completely sealed aluminum body.
- **Operates in Extreme Temperatures:** -67°F to +185°F
- **Tamper Resistant Screws** and standard faceplate mounting screws are included.
- **Weatherproof Faceplate Gasket** included. All models mount on single-gang box. Specify BBX option to include a weatherproof surface back box.
- **Lifetime Warranty:** Made in the USA by DynaLock, with over 20 years experience in the manufacture of electronic security & access control products.

# 6170 Series Weatherproof Pushbutton

## Model Selection




All models are momentary-action and include green LED backlit button (shown illuminated).

## Options

- BBX** Weatherproof Surface Back Box - 2<sup>5</sup>/<sub>8</sub>" deep
- CSF** Custom Silkscreened Faceplate - Consult factory for price and delivery
- SF** Special Finish Faceplate - US32D standard, consult price book for other finishes

## Specifications

- Output Contacts: Form Z (SPDT-Double Break)   
3A @ 115VAC / UL
- LED Backlight: Green  
10mA @ 12/24VDC (Selectable)
- Ratings: Water-tight to IP68  
Moisture-proof to IP64  
Dust-tight to IP64
- Operating Temp: -67°F to +185°F
- Terminations: 7" color coded 18 AWG leads

**DYNALOCK CORPORATION**  
705 EMMETT STREET / PO BOX 2728  
BRISTOL, CT 06011-2728  
PHONE: 877-DYNALOCK / FAX: 860-585-0338  
E-MAIL: INFO@DYNALOCK.COM  
WEBSITE: WWW.DYNALOCK.COM

Featuring  
  
**DynaLife**<sup>®</sup>  
Lifetime Warranty